

# WIDEX DREAM™ RIC WITH S-RECEIVER AND **TRUEISP**


## 4 PERFORMANCE LEVELS 440/330/220/110



The WIDEX DREAM RIC uses our unique wireless WidexLink technology and the new TRUE ISP, True-Input technology platform. Volume control and program shift via RC-DEX/M-DEX. Uses a size 10 battery.

Minimal to severe hearing losses

### SUGGESTED FITTING RANGE



### STANDARD TECHNOLOGY

- **TRUEISP**
- True-Input technology
- WidexLink - Wireless connectivity
- InterEar functionality
- Multiple earware options

KEY FEATURES	440	330	220	110
Performance	xxxxx	xxxx	xxx	xx
Processing channels	15	10	5	3
TruSound Softener	X	X		
HD Locator/Locator	HD	HD	HD	X
Feedback cancelling (IE-InterEar)	IE	IE	IE	
Digital Pinna	X	X		
Speech Enhancer (IE-InterEar)	IE	X		
Personal Audibility Extender	X	X	X	X
Personal Acclimatisation	X	X	X	X
Number of programs*	5	4	3	2
Personal Zen	IE			
InterEar Partner Monitor	IE			
Reverse focus	X	X	X	
SmartSpeak/SmartTone	X	X	X	X

DEX ACCESSORIES	X	X	X	X
RC-DEX, TV-DEX, M-DEX, FM+DEX, PHONE-DEX <sup>1</sup>				

\* Plus Zen+


<sup>1</sup> Available in Europe

# D-PA

## MAXIMUM OUTPUT - EAR SIMULATOR

IEC 60118-0


Output dB SPL



## MAXIMUM OUTPUT - 2CC COUPLER

IEC 60118-7 / ANSI S3.22-2009


Output dB SPL



## OUTPUT - EAR SIMULATOR

IEC 60118-0


Output dB SPL



## OUTPUT - 2CC COUPLER

IEC 60118-7 / ANSI S3.22-2009

Output dB SPL



**Technical data** Typical data obtained through standard pure tone measurements.  
Hearing aid set to Compass Test mode 1, unless stated otherwise.  
Measured using a standard ITE coupler without wax guard.

		IEC 60118-0	ANSI S3.22-2009 / IEC 60118-7
OSPL90	2500 Hz	114 dB SPL	103 dB SPL
	Peak	120 dB SPL	108 dB SPL
	Average	111 dB SPL	102 dB SPL
Acoustic output (Input 60 dB SPL)	2500 Hz	93 dB SPL	83 dB SPL
	Peak	95 dB SPL	84 dB SPL
	Average	85 dB SPL	79 dB SPL
Max gain (Input 50 dB SPL, Compass Max gain test mode)	2500 Hz	62 dB	51 dB
	Peak	62 dB	52 dB
	Average	58 dB	50 dB
Frequency range		100 Hz - 10000 Hz	100 Hz - 8400 Hz
Harmonic distortion (Input 70 dB SPL)	500 Hz	<2%	<2%
	800 Hz	<2%	<2%
	1600 Hz	<2%	<2%
Equivalent input noise		21 dB SPL	25 dB SPL
Battery drain (stand by)		0.98 mA	0.98 mA
Battery drain		0.98 mA	0.99 mA
Battery life / hours (Type 10 Zn-Air, 90 mAh)		90 (>85)	90 (>85)
Mobile phone immunity		IRIL: -30/3 dB SPL	U-rating: M4

